



QuietTorque™ 30.0 LC

Clean, Green, and Quiet!


*Electric propulsion systems engineered
and built by sailors for sailors since 2007!*

The **QuietTorque™ 30.0 LC** is recommended for boats up to 45' (LOA) and 28,000lbs displacement. Liquid cooling provides for high sustained output, ideal for hybrid applications. Typical battery size is 300 - 500Ah.

Specifications

Motor type	2 PMAC Brushless
Voltage	48Vdc (nom)
Max. Input Power	30 kW
Cont. Input Power	25 kW
Weight	180 pounds
Frame	Anodized Aluminum

*Permanent magnet Alternating Current



Standard Features

Motor Mounts	Adjustable Mounts to current engine stringers
Throttle	Anodized Al waterproof throttle with key & neutral lock
System Monitor	Programmable digital display <ul style="list-style-type: none">• State of Charge (SOC)• Voltage, Current, Power and RPM• Time to Discharge (TTD)• Programmable regeneration and max power• Programmable RH or LH propeller rotation• Programmable for flooded, AGM and LiFePO4 battery type and size
Shaft coupler	4" flange (Hurth/Borg Warner)
Power Switch	Two position 500A GigaVac switch
Relay	500amp TE Connectivity vacuum relay
Fuse	Class-T fuse & holder



Why Electric Yacht

- UNPARALLELED CUSTOMER SERVICE AND ENGINEERING
- Computer generated performance projections
- Three year warranty
- Designed for customer installation

The **QuietTorque™ 30.0 LC** is very complete and includes everything needed except batteries, battery cables and charger. Contact us directly or through one of our dealers and we will help you design a complete system to meet your particular needs.